



US007073686B2

(12) **United States Patent**  
**Hanell**

(10) **Patent No.:** **US 7,073,686 B2**  
(45) **Date of Patent:** **Jul. 11, 2006**

(54) **POURING SPOUT**

(76) **Inventor:** Edward G. Hanell, 2457 Louella Ave.,  
Venice, CA (US) 90291

(\*) **Notice:** Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(h) by 386 days.

(21) **Appl. No.:** 10/619,903

(22) **Filed:** Jul. 15, 2003

(65) **Prior Publication Data**

US 2005/0011909 A1 Jan. 20, 2005

(51) **Int. Cl.**  
**B67D 5/00** (2006.01)

(52) **U.S. CL.** 222/83.5; 222/541.2; 220/267;  
229/204

(58) **Field of Classification Search** 222/541.5,  
222/5, 525, 80-90, 241.5, 556, 541.2; 220/267;  
229/204

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,325,828 A \* 12/1919 Becker-Jurgen et al. .... 222/90  
1,826,838 A \* 10/1931 Stump et al. .... 222/90  
3,258,168 A 6/1966 Kochler, Jr.  
3,599,836 A 8/1971 Hegi  
3,602,396 A 8/1971 Oates  
3,961,732 A 6/1976 Roberts  
3,964,640 A 6/1976 Laughlin  
4,009,805 A 3/1977 Klygis et al.  
4,150,768 A 4/1979 Maynard, Jr.

4,205,757 A 6/1980 Jurgens  
4,271,983 A \* 6/1981 Takemura et al. .... 222/85  
4,399,929 A 8/1983 Scaglione  
4,446,989 A 5/1984 Brannen  
4,881,662 A 11/1989 Tallman  
5,020,690 A \* 6/1991 Kishikawa et al. .... 222/83  
5,147,070 A \* 9/1992 Iwamoto .... 222/83  
5,195,662 A 3/1993 Neff  
5,213,239 A 5/1993 Macaluso  
5,249,708 A 10/1993 Magness  
5,366,114 A 11/1994 Bernstein et al.  
5,573,047 A 11/1996 Akin  
5,579,963 A 12/1996 Murthi  
5,960,992 A \* 10/1999 Bernstein et al. .... 222/83.5  
6,003,715 A 12/1999 Harris

\* cited by examiner

*Primary Examiner*—Michael Mar

*Assistant Examiner*—Melvin Cartagena

(74) *Attorney, Agent, or Firm*—John S. Christopher

(57) **ABSTRACT**

A pouring spout for use in providing a conduit for the discharge of the contents of a closed container containing fluids or granulated materials includes a cylindrical inner housing having an open top end and a removable tethered cap. A pair of opposing punch blades affixed to the cylindrical inner housing is provided for insertion into a top surface of a container where the cylindrical inner housing and the punch blades serve to provide a discharge conduit for the container. A projection spur is formed on each of the punch blades for forcing open the top surface of the container. An outer safety sleeve is provided for covering the punch blades when the punch blades are withdrawn from the top surface of the container.

20 Claims, 4 Drawing Sheets

